

Product Specification Prime Nouveau

Description:	Fine Gauge, Textured Loop Pile
Pile Fibre:	100% Selected Carpet Wools
Fibre Quality:	Woollen Spun, Multi-ply, Twisted and Non Set
Gauge:	2.54 mm (1/10")
Stitch Rate:	29.0 per 100mm
Pile Mass:	1763 gm/m ² (52 oz/yd ²)
Pile Height:	10.0 mm
Colouration:	Stock Dyed and Solution Dyes
Pattern Repeat:	N/A
Primary Backing:	112 g/m ² (3.3 oz/yd ²) Woven Polypropylene
Secondary Backing:	237 g/m ² (7 oz/yd ²) Woven Jute
Laminate:	948 g/m ² (28 oz/yd ²) Synthetic Latex
Total Weight:	11.2 kg/LM (90.3 oz/yd ²)
Width:	3.66 metres
A.C.C.S. Reg. No.:	25167
A.C.C.S. Grade:	Residential Extra Heavy Duty 2 (Stairs) – 6 star Contract Extra Heavy Duty (Stairs) - 4 star
Critical Radiant Flux: (Burning Behaviour)	CHF Mean Result: 7.5 kw/m ² (Conventional Laid) Smoke Value: 67 % min (Conventional Laid)
AS/ISO 9239-1:2003 Part 1 - Test	Passes requirements of BCA spec C1.10a Class 9a; 9b; 9c Buildings (Direct Stick)
BS 1006.B02:	Colourfastness to light 5
AS 2111.19.2:	Colourfastness to shampoo 3-4
AS 2111.19.1:	Colourfastness to rubbing 3-4
AS 2111.4.16:	Colourfastness to solvents 3-4
Product Features:	<ul style="list-style-type: none"> • 6 Contemporary neutral contract colourations • Increases thermal and acoustic comfort. • Superior appearance when correctly maintained. • The use of chair pads is mandatory when used in commercial installations. • Virtually unlimited custom colour option. • Must be laid in accordance with AS/NZS 2455.1.2007 • Subject to Tuftmaster's 'Terms of Trading.'